

With over 10 years experience in design, testing and racing we are an industry leader when it comes to

Generally you have several options available when selecting a triple clamp such as

- Solid or Rubber Mounted Bar Mounts (Most models)
- Bar Clamp Configuration (Moto, SX, Scotts or SUB Mount)
- Bar Mount Handlebar Size (7/8" or 1 1/8")
- Bar Mount Height (1.240", 1.360", 1.640")
- Bar Position (Relative to [PSA](#) Stem)"
- Special Offsets (Available for certain models only)

[VIEW RTS CHART](#)

{yoogallery src=[/media/imgs/prod_info_imgs/tc_info_imgs/viewer/] width=[100]}

BRP triple clamps are the only triple clamps on the market that are exclusively designed for mounting a

BRP triple clamps are manufactured to the highest quality standards from 6061-T6 billet aluminum mak

Bar Clamp and Bar Mount Configurations

We offer 4 different bar mount configurations; Moto, SX, Scotts and SUB Mount. The Moto, SX and Sco

Moto Bar Mounts



SV Bar Mounts



Scotts Bar Mounts



SUB Mount



Handlebar Position Options

All triple clamps and bar mount configurations are different. At BRP most of our triple clamps offer a farth

Along with the image on [Bar Position Page](#), bar position charts and the information you need to select the b



TRIPLE CLAMP OFFSET DIAGRAM

